


## SOUND PROOFING

This is a closed cell, Vinyl Nitrile, medium density sponge material. It will not absorb fluids because of its closed cell construction. It is very easy to work with, it will conform to any shape and mold around anything. For installation we recommend a high heat release contact cement. It is available as the raw material or it can be purchased with a foil finish on one side. The foil finish gives it a great look for any application that will cause it to be exposed or when it may be necessary to have added protection on the exposed side. This material has been tested and does comply with the FAA requirements of the FAR 25.853B burn test.



<a href="#">T-45093-1/8</a>	1/8" x 36" x 56"
<a href="#">T-45093-3/8</a>	3/8" x 36" x 56"
<a href="#">T-45093-5/8</a>	5/8" x 36" x 56"

### FOIL BACKED



<a href="#">CT-11809-3/8</a>	3/8" x 36" x 56"
<a href="#">CT-11809-5/8</a>	5/8" x 36" x 56"

## WOOL FELT

The **T-730** is a high density wool felt used for insulation and sound dampening. It is a compressed wool manufactured to meet the MF5656A Type III specification. We stock many different thickness and they are available either in a sheet or a roll.

### ROLLS



<a href="#">T-730-1/16R</a>	1/16' x 2" x 10 FT
<a href="#">T-730-1/8R</a>	1/8" x 2" x 10 FT
<a href="#">T-730-1/4R</a>	1/4" x 2" x 10 FT
<a href="#">T-730-3/8R</a>	3/8" x 2" x 10 FT
<a href="#">T-730-1/2R</a>	1/2" x 2" x 10 FT
<a href="#">T-730-3/4R</a>	3/4" x 2" x 10 FT

### SHEETS

<a href="#">T-730-1/16S</a>	1/16" x 36" x 36"
<a href="#">T-730-1/8S</a>	1/8" x 36" x 36"
<a href="#">T-730-1/4S</a>	1/4" x 36" x 36"
<a href="#">T-730-3/8S</a>	3/8" x 36" x 36"
<a href="#">T-730-1/2S</a>	1/2" x 36" x 36"
<a href="#">T-730-3/4S</a>	3/4" x 36" x 36"
<a href="#">T-730-1S</a>	1" x 36" x 36"



## 1/8" INSULATION TAPE

This is a closed cell, high density, firm synthetic sponge rubber, it has an adhesive backing for easy installation. It is a multi-purpose tape that can be used for either a

gap seal, window installation tape or a chafe tape. It is 1/8" thick and available in various lengths.



<a href="#">T-5090-10FT</a>	1/8" x 2" x 10 FT
<a href="#">T-5090-30FT</a>	1/8" x 2" x 30 FT
<a href="#">T-5090-4</a>	1/8" x 1/4" x 30 FT
<a href="#">T-5090-8</a>	1/8" x 1/2" x 30 FT
<a href="#">T-5090-16</a>	1/8" x 1/2" x 30FT

## ADHESIVE BACKED CORK

This is an adhesive backed cork material manufactured to meet the MIL-T-6841 spec. It is comprised of a Buna- Rubber/ cork blend material with a PSA on the back of one side. It is sold in sheets 36" x 36". This material can be cut into strips, shapes or used for making gaskets where a PSA backing in desired.



<a href="#">CK-115-1/4</a>	36" x 36" x 1/4"
<a href="#">CK-115-1/8</a>	36" x 36" x 1/8"
<a href="#">CK-115-1/16</a>	36" x 36" x 1/16"
<a href="#">CK-115-1/32</a>	36" x 36" x 1/32"

## 1/4" INSULATION TAPE

This is a closed cell, high density, firm synthetic sponge rubber, it has an adhesive backing for easy installation. It is a multi-purpose tape that can be used for either a gap seal or a chafe tape. It is 1/4" thick and available in either a sheet or Roll.

<a href="#">T-2002-16</a>	1/4" x 1" x 20 FT
<a href="#">T-2002-8</a>	1/4" x 1/2" x 20 FT
<a href="#">T-2002-36</a>	1/4" x 36" x 36"